

XHTML Cheat Sheet v. 1.03

%attrs %coreattrs %i18n %events %coreattrs id class style title %i18n xml:lang lang dir %events onclick ondblclick onmousedown onmouseup onmouseover onmousemove onmouseout onkeypress onkeydown onkeyup %focus accesskey tabindex onfocus onblur input types text password checkbox radio submit image reset button hidden file link types (rel, rev) alternate stylesheet start next prev contents index glossary copyright chapter section subsection appendix help bookmark media descriptors screen tty tv projection handheld print braille aural all	BLOCK ELEMENTS			deprecated elements applet center dir menu basefont font isindex s strike u entities " " & & < < > > ' ' (space) i ¡ ¢ ¢ £ £ ₣ ¤ ¥ ¥ ¦ ¦ § § ¨ ¨ © © ª ª « « ¬ ¬ - (cond.) ­ ® ® ¯ ¯ ° ° ± ± ¹ ¹ ² ² ³ ³ ´ ´ µ µ ¶ ¶ · · ¸ ¸ º º » » ¼ ¼ ½ ½ ¾ ¾ ¿ ¿ À À Á Á Â Â Ã Ã Ä Ä Å Å Æ Æ Ç Ç È È É É Ê Ê Ë Ë Ì Ì Í Í Î Î Ï Ï Ð Ð Ñ Ñ Ò Ò Ó Ó Ô Ô Õ Õ Ö Ö
	address	information on author	%attrs	
	blockquote	long quotation	%attrs, cite	
	div	generic container (block)	%attrs, align*	
	dl	definition list	%attrs, compact*	
	fieldset	form control group	%attrs	
	form	interactive form	%attrs, action , method, enctype, accept, name*, onsubmit, onreset, accept-charset, target*	
	h1-h6	six levels of headings	%attrs, align*	
	hr	horizontal rule	%attrs, align*, size*, width*, noshade*	
	noframes*	alternate content for non frame-based rendering	%attrs	
	noscript	content when scripts disabled	%attrs	
	ol	ordered list	%attrs, type*, start*, compact*	
	p	paragraph	%attrs, align*	
	pre	preformatted text	%attrs, width*	
	ul	unordered list	%attrs, type*, compact*	
	INLINE ELEMENTS			
	a	anchor (or link)	%attrs, charset, type, name, rel, rev, href, hreflang, target*, shape, coords, %focus	
	abbr	abbreviation	%attrs	
	acronym	acronym (UNO, NATO,...)	%attrs	
	b	bold text	%attrs	
	bdo	I18N BiDi over-ride	%coreattrs, %events, xml:lang, lang, dir	
	big	large font	%attrs	
	br	forced line break	%coreattrs, clear*	
	button	push button	%attrs, name, value, type, disabled, %focus	
	cite	citation or reference	%attrs	
	code	computer code	%attrs	
	dfn	definition	%attrs	
	em	emphasis	%attrs	
	i	italic text	%attrs	
	iframe*	inline subwindow	%coreattrs, londes, name, src, frameborder, marginwidth, marginheight, scrolling, align*, height, width	
	img	embedded image	%attrs, src , alt , longdesc, name, height, width, usemap, ismap, align*, border*, hspace*, vspace*	
	input	form control	%attrs, type, name, value, checked, disabled, readonly, size, maxlength, src, alt, ismap, usemap, onselect, onchange, accept, %focus, align*	
	kbd	text to be entered by the user	%attrs	
	label	form field label text	%attrs, for, accesskey, onfocus, onblur	
	map	client-side image map	%i18n, %events, id , class, style, title, name	
	object	generic embedded object	%attrs, declare, classid, codebase, data, type, codetype, archive, standby, height, width, usemap, name, tabindex, align*, border*, hspace*, vspace*	
	q	short inline quotation	%attrs, cite	
	samp	sample output from scripts	%attrs	
	select	option selector	%attrs, name, size, multiple, disabled, tabindex, onfocus, onblur, onchange	

&times; &Oslash; &Ugrave; &Uacute; &Ucirc; &Uuml; &Yacute; &THORN; &szlig; &agrave; &aacute; &acirc; &atilde; &auml; &aring; &aelig; &ccedil; &egrave; &eacute; &ecirc; &euml; &igrave; &iacute; &icirc; &iuml; &eth; &ntilde; &ograve; &oacute; &ocirc; &otilde; &ouml; &divide; &oslash; &ugrave; &uacute; &ucirc; &uuml; &yacute; &ythorn; &yuml; &forall; &part; &exist; &empty; &nabla; &isin; &notin; &ni; &prod; &sum; &minus; &lowast; &radic; &prop; &infin; &ang; &and; &or; &cap; &cup; &int; &there4; &sim; &cong; &asymp; &neq; &equiv; &leq; &geq; &sub; &sup; &sub;	small span strong sub sup textarea tt var TABLE ELEMENTS caption col colgroup table tbody td tfoot th thead tr OTHER ELEMENTS area base body dd del dt frame frameset head html ins legend li link meta optgroup option param script style title	small font generic container (inline) indicates stronger emphasis subscript superscript multi-line text field teletype or monospaced text instance of a variable or program argument table caption table column table column group table element (block) table body table data cell table footer table header cell table header table row image map area document base URI document body definition description deleted text definition term subwindow window subdivision document head root element inserted text fieldset legend list item media-independent link generic metainformation option group selectable choice named property value script statements style info document title	%attrs %attrs %attrs %attrs %attrs %attrs, name, rows, cols, <i>disabled</i>, <i>readonly</i>, <i>onselect</i>, <i>onchange</i>, %focus %attrs %attrs %attrs, align* %attrs, span, width, valign, align, char, charoff %attrs, span, width, valign, align, char, charoff %attrs, summary, width, border, frame, rules, cellpadding, cellspacing, align*, bgcolor* %attrs, align, char, charoff, valign %attrs, abbr, axis, headers, scope, rowspan, colspan, align, char, charoff, valign, bgcolor*, <i>nowrap*</i>, width*, height* %attrs, align, char, charoff, valign %attrs, abbr, axis, headers, scope, rowspan, colspan, align, char, charoff, valign, bgcolor*, <i>nowrap*</i>, width*, height* %attrs, align, char, charoff, valign %attrs, align, char, charoff, valign, bgcolor* href, id, target* %attrs, onload, onunload, background*, bgcolor*, text*, link*, vlink*, alink* %attrs %attrs, cite, datetime %attrs %coreattrs, longdesc, name, src, frameborder, marginwidth, marginheight, <i>noresize</i>, scrolling %coreattrs, rows, cols, onload, onunload %i18n, id, profile xmlns= "http://www.w3.org/1999/xhtml", id, %i18n, version* %attrs, cite, datetime %attrs, accesskey, align* %attrs, type*, value* %attrs, charset, href, hreflang, type, rel, rev, media, target* %i18n, id, http-equiv, name, content, scheme %attrs, <i>disabled</i>, label %attrs, <i>selected</i>, <i>disabled</i>, label, value id, name, value, valuetype, type id, charset, type, src, <i>defer</i>, language* %i18n, id, type, media, title %i18n, id	⊆ &sube; ⊇ &supe; ⊕ &oplus; ⊗ &otimes; ⊥ &perp; ⋅ &sdot; ⋄ &lloz; [&lceil;] &rceil; ⌊ &lfloor; ⌋ &rfloor; ⟨ &lang; ⟩ &rang; ← &larr; ↑ &uarr; → &rarr; ↓ &darr; ↔ &harr; ↶ &crarr; ↷ &lArr; ⇕ &uArr; ⇒ &rArr; ⇓ &dArr; ⇔ &hArr; • &bull; ′ &prime; — &oline; / &frasl; ↯ &weierp; ↬ &image; ℔ &real; ™ &trade; € &euro; ℵ &alefsym; ♠ &spades; ♣ &clubs; ♥ &hearts; ♦ &diams; &ensp; &emsp; &thinsp; &zwj; &zwj; &lrn; &rlm; — &ndash; — &mdash; ` &lsquo;</div><div>` &rsquo; ` &sbquo; “ &lquo; ” &rquo; „ &bdquo; † &dagger; ‡ &Dagger; … &hellip; ‰ &permil; < &lsaquo; > &rsaquo; * deprecated or not allowed in Strict DTD if allowed in Transitional DTD fixed value attribute required backslash attribute
--	--	---	---	--