

Mathematical

ABS
SIGN
MOD
FLOOR
CEILING
ROUND
DIV
EXP
LN
LOG, LOG2, LOG10
POW
POWER
SQRT
PI
COS
SIN
TAN
ACOS
ASIN
ATAN, ATAN2
COT
RAND
LEAST
GREATEST
DEGREES
RADIANS
TRUNCATE

Date and Time

DAYOFWEEK
WEEKDAY
DAYOFMONTH
DAYOFYEAR
MONTH
DAYNAME
MONTHNAME
QUARTER
WEEK
YEAR
YEARWEEK
HOUR
MINUTE
SECOND
PERIOD_ADD
PERIOD_DIFF
DATE_ADD
DATE_SUB
ADDDATE
SUBDATE
EXTRACT
TO_DAYS
FROM_DAYS
DATE_FORMAT
TIME_FORMAT
CURRENT_DATE
CURRENT_TIME
NOW
SYSDATE
UNIX_TIMESTAMP
FROM_UNIXTIME
SEC_TO_TIME
TIME_TO_SEC

Group

COUNT
AVG
MIN
MAX
SUM
GROUP_CONCAT
VARIANCE
STD
STDDEV
BIT_OR
BIT_AND

**DATA TYPES**

CHAR	String, length 0 - 255
VARCHAR	String, length 0 - 255
TINYTEXT	String, length 0 - 255
TEXT	String, length 0 - 65535
BLOB	String, length 0 - 65535
MEDIUMTEXT	String, length 0 - 16777215
MEDIUMBLOB	String, length 0 - 16777215
LONGTEXT	String, length 0 - 4294967295
LOBLOB	String, length 0 - 4294967295
* TINYINT	Integer, -128 to 127
* SMALLINT	Integer, -32768 to 32767
* MEDIUMINT	Integer, -8388608 to 8388607
* INT	Integer, -2147483648 to 2147483647
* BIGINT	Int, -9223372036854775808 to 9223372036854775807
FLOAT	Decimal (precise to 23 digits)
DOUBLE	Decimal (24 to 53 digits)
DECIMAL	"DOUBLE" stored as string
DATE	YYYY-MM-DD
DATETIME	YYYY-MM-DD HH:MM:SS
TIMESTAMP	YYYYMMDDHHMMSS
TIME	HH:MM:SS
ENUM	One of preset options
SET	Selection of preset options
* Note: "UNSIGNED" TINYINT, SMALLINT, MEDIUMINT, INT, BIGINT have the same range of values but start at 0, e.g. TINYINT UNSIGNED is between 0 and 255.	

MYSQL FUNCTIONS IN PHP

mysql_affected_rows
mysql_close
mysql_connect
mysql_data_seek
mysql_db_name
mysql_errno
mysql_error
mysql_fetch_array
mysql_fetch_assoc
mysql_fetch_field
mysql_fetch_lengths
mysql_fetch_object
mysql_fetch_row
mysql_field_flags
mysql_field_len
mysql_field_name
mysql_field_seek
mysql_field_table
mysql_field_type
mysql_free_result
mysql_insert_id
mysql_list_dbs
mysql_list_processes
mysql_list_tables
mysql_num_fields
mysql_num_rows
mysql_pconnect
mysql_query
mysql_real_escape_string
mysql_select_db

SAMPLE SELECT QUERIES

SELECT * FROM tablename	# Returns all columns
SELECT column FROM tablename	# Returns specific column
SELECT COUNT(*) FROM tablename	# Returns number of rows
SELECT SUM(column) FROM tablename	# Returns sum of column
SELECT DISTINCT column FROM tablename	# Returns unique values of column
SELECT * FROM tablename WHERE condition	# Returns rows that match condition
SELECT * FROM tablename WHERE BINARY condition	# Condition is case-sensitive
SELECT * FROM table1 INNER JOIN table2 on table1.id = table2.id	# Join two tables, return all columns
SELECT table1.* FROM table1 INNER JOIN table2 on table1.id = table2.id	# Only return columns from table1
SELECT LAST_INSERT_ID() as new_id	# Returns ID of last created row
SELECT max(column) AS alias	# Return maximum value in column as "alias"
SELECT * FROM table ORDER BY column	# Return all rows ordering by column
SELECT * FROM table LIMIT 10, 20	# Return first 20 rows after row 10

Control Flow

IFNULL
NULLIF
IF

String

ASCII
ORD
CONV
BIN, OCT, HEX
CHAR
CONCAT
CONCAT_WS
LENGTH
CHAR_LENGTH
BIT_LENGTH
LOCATE
INSTR
LPAD
RPAD
LEFT
RIGHT
SUBSTRING
MID
SUBSTRING_INDEX
LTRIM
RTRIM
TRIM
SOUNDEX
SPACE
REPLACE
REPEAT
REVERSE
INSERT
ELT
FIELD
LCASE
UCASE
LOAD_FILE
QUOTE

Comparison

STRCMP

Cast

CAST
CONVERT

Other

BIT_COUNT
DATABASE
USER
SYSTEM_USER
SESSION_USER
CURRENT_USER
PASSWORD
OLD_PASSWORD
ENCRYPT
DECODE
MD5
SHA1
AES_ENCRYPT
AES_DECRYPT
DES_ENCRYPT
DES_DECRYPT
LAST_INSERT_ID
FORMAT
VERSION
CONNECTION_ID
GET_LOCK
RELEASE_LOCK
IS_FREE_LOCK
BENCHMARK
INET_NTOA
INET_ATON
FOUND_ROWS